



**MODEL 6100-45-CTA
HEAVY DUTY TURNTABLE CONVEYORIZED AUTOMATIC
STRETCH WRAP SYSTEM GENERAL SPECIFICATIONS**

PRODUCTION SPEED

- 1-45 loads per hour

NOTE: Process rates will vary with load size, number of wraps & conveyor speed

LOAD CAPACITY

- Maximum load weight: 4,000# dynamic – 12,000# static
 - Maximum load size: 50" W x 50" L (71" max. load diagonal) x 82" H (plus up to 4" top overlap)
 - Minimum load size: 30" W x 30" L x 24" H
-

TURNTABLE

- 80" diameter skirted turntable
 - 4,000# dynamic weight capacity
 - 29" diameter ring gear support system, direct pinion-to-gear drive
 - 1-15 RPM rotational speed c/w soft start acceleration
 - Final revolution deceleration and positive stop alignment
 - 1 HP DC variable speed motor c/w turntable holding brake
 - Remote centralized lubrication for ring gear
-

**FILM CARRIAGE
ELEVATOR**

- 1/2 HP DC variable speed motor
 - ANSI #40 direct chain drive c/w shock dampener & **Anti-Fall Safety Device**
 - Maintenance free 12 point carriage guidance system
-

**FILM DELIVERY
SYSTEM**

- **NEW Super Rapid Thread II**™ 20" capacity pre-stretch film carriage
 - *Special Film Threading Device – Uniquely orientates the sticky side of the film against the pre-stretch rollers and the inside of the load*
 - 1/2 HP DC variable speed motor
-

FILM DELIVERY SYSTEM
...continued...

- Fully electronic dynamic dancer corner compensation
- 33% to 313% fixed stretch capability
- Pre-stretch ratio variable using easy sprocket change
- **Carriage Descent Obstruction Safety Shut-Off Device**
- **Rapid Thread™ Safety Door with auto power cut-off switch**
- Superior *film-to-roller* contact area
- Lifetime warranty on pre-stretch rollers

POWERED ROLLER CONVEYOR

Basic system: 5ft Infeed section, 80" diameter turntable section & 5ft Exit section

Each section includes:

- Chain driven live roller conveyor rated 4,000# per section
- 2-1/2" diameter 11 gauge rollers c/w 11/16" hex axles on 3" centers
- ANSI # 40 roller to roller chain drive
- 54" effective roller width
- Conveyor speeds 20 to 50 FPM (specify required speed) with electronic soft start
- Pass-line height – 18" from floor to top of rollers
- 1/2 HP AC variable speed reversible TEFC motor (turntable conveyor motor is 1/2 HP DC)
- Automatic load indexing and centering by photo-eye & PLC logic

CONTROL FEATURES

- **PANASONIC** FP-X Programmable Logic Controller (PLC)
- HMI Touchscreen Operator Interface Panel
- Illuminated Power Start / Reset button
- Emergency Stop button
- Wrap Cycle Start (rewrap) button
- Manual controls provided for turntable jog, film carriage elevator lower/raise, film clamp open/close and conveyors forward/reverse
- Wrap Bypass mode selector switch
- Separate film carriage elevator raise & lower speed controls
- Film tension (force-to-load) control
- Separate 1 to 12 revolution top & bottom wrap control
- Triple beam auto load height sensing photo-eye, detects dark or shiny loads

CONTROL FEATURES ...continued...	<ul style="list-style-type: none">• Broken film/out of film detection c/w automatic machine reset and fault beacon light• Turntable drive and film carriage elevator dynamic braking• NEMA 12 control panel and junction boxes• Dust tight slip ring assembly• Non-proprietary UL/CSA approved components
AUTOMATION FEATURES	<ul style="list-style-type: none">• Pneumatically actuated film clamp mechanism• Pneumatically actuated film tail cut/wiper arm mechanism• Ni-chrome impulse hot wire film cut off c/w automatic periodic cleaning cycle
STRUCTURAL FEATURES	<ul style="list-style-type: none">• All structural steel construction• Forklift truck portable base structure design• Structural steel H-beam machine tower• Electro-static powder coated paint finish
SAFETY FEATURES	<ul style="list-style-type: none">• Safety barriers enclose the turntable section to prevent personnel intrusion• Operator Access Gate c/w Safety Interlock Switch disables machine operation when gate is opened• Hard-wired emergency stop and operator access gate circuits with Category 3 dual channel safety relays
ELECTRICAL INPUT REQUIREMENT	<ul style="list-style-type: none">• 208Y/120 Volts 3 Phase 60 Hz 30 Amps (other voltages available – consult factory)
PNEUMATIC REQUIREMENT	<ul style="list-style-type: none">• 3 CFM @ 80 PSI clean dry pneumatic supply required• Filter/regulator c/w gauge & lock-out valve provided
TYPICAL SYSTEM DIMENSIONS	<ul style="list-style-type: none">• 202" (L) x 143" (W) x 100" (H) (Standard dimensions are approximate)
