

# The A-Arm Fully Automatic Stretch Wrapper Makes Your Buying Decision Easy!



DATE: May 2013

<b>SWITCH WITH A-ARM Full Automation Technology MODELS HP-SWA &amp; LP-SWA STANDARD FEATURES</b>	<b>COUSINS A-ARM</b>	<b>LANTECH Q300XT</b>	<b>WULFTEC SMLPA-200-S</b>	<b>ORION FLEX LPA</b>	<b>ARPAC PA-Series LP</b>
The ability to be easily converted from our semi-automatic model to this fully automatic on site at a later date	YES	NO	NO	NO	NO
Has a unique and patented grip/cut device that eliminates of a hard to maintain clamp on the turntable and hotwire cutting device	YES	has a clamp on the turntable	has a clamp hotwire cut	has a clamp hotwire cut	has a clamp hotwire cut
All electric – does not require air	YES	YES	requires air	requires air	requires air
65” diameter turntable with heavy duty surround deck – model LP-SWA	YES	No surround deck	YES	YES	NO
The ending tail is at the top of the load so it will not drag on the floor getting tangled in material handling equipment	YES	NO	NO	NO	NO
4500# turntable capacity	YES	NO	YES	YES	NO
All AC variable frequency drives and motors	YES	NO	YES	YES	NO
A unique pre-stretch film carriage that provides maximum film-to-rubber roller contact. The threading method always places the sticky side of the film against <u>both</u> the rubber rollers and the load.	YES	NO	NO	NO	NO
HMI operator interface with diagnostic ability	YES	NO	NO	YES	NO
Anti-fall devices for both film carriage and optional A-Arm	YES	NO	NO	NO	NO
Safety electrical interlock that shuts the power off when the access door is opened for film threading.	YES	NO	NO	NO	YES
Film carriage anti-descent plate – stops the carriage movement if obstacle is detected	YES	NO	NO	YES	NO

**Note:** This information is based on competitive information available to the public and may be incorrect because of recent changes to specifications. Please check with the manufacturer for any recent revisions to their specifications.